

Toplex Flow Pack

Engineered to Outperform

Films for VFFS and HFFS
packaging equipment



Overview

Our range of co-extruded and laminated Flow Pack films is optimized to work trouble free for vertical (VFFS) and horizontal (HFFS) form, fill and seal packaging machines.

Flow Pack films are engineered to gain maximum production efficiency through increased throughput and speed, while functioning to extend shelf life and offer premium shelf presentation.

Technology

Multilayer film manufactured in a combination of blown extrusion technology and lamination processes.

The outer layers of the films feature low COF and good sealing properties, allowing the film to outperform on various flow pack applications.

With add-ons, such as printing and laser perforation, a simple package may easily be upgraded.

Features & Properties

- Excellent stiffness allows easier machinability
- Available for impulse or constant heat sealing bars
- Excellent smoothness, very low coefficient of friction for easier flow in the packaging machine
- Sealing through product residue at a wide range of temperatures
- Excellent hot tack for demanding weight and drop height
- Outstanding optical properties, clarity and gloss

- Available anti-fog properties
- Wide range of printing options: surface or trapped printing, random or registered
- Available in different barrier levels for range of food products
- Available for impulse or constant heat sealing bars
- Available for fin or lap seals

Applications

Suitable for most available VFFS and HFFS packaging equipment in the market

Food Segments

Ideally suited for packaging shredded and grated cheese, sausages, salad mixes, frozen vegetables, whole or cut vegetables and fruits



Product Range

PRODUCT	THICKNESS [micron]	BARRIER LEVEL	SEALING BAR	PACKAGING MACHINE
TOPLEX HB L-PE	45/60/80	HB	Constant Heat	HFFS + VFFS
TOPLEX HB	60/80	HB	Constant Heat	HFFS
TOPLEX LB L-PE	45/60/80	LB	Constant Heat	HFFS + VFFS
TOPLEX TNN 445/460/480	45/60/80	HB	Constant Heat	HFFS + VFFS
TOPAZ	21-80	Range	Constant Heat	HFFS + VFFS
TARIBO T60	60	Permeable	Impulse	VFFS
TARIBO BOPP	30-40	Permeable	Constant heat/impulse	HFFS + VFFS



www.plastopil.com

EUROPE

Plastopil B.V.

De Steiger 46
1351 AC Almere
The Netherlands

T. +31 36 767 1000
F. +31 36 540 4800

ISRAEL

Plastopil Hazorea Company Ltd.

Hazorea 3658100
Israel

T. +972 4 959 8800
F. +972 4 989 4250

NORTH AMERICA Plastopil Inc.

838 Lincoln Ave.
Maywood, NJ 07607
U.S.A.

T. +1 551 427 8668
F. +1 201 250 8538