

Toplex Locked Seal

Sealing in the Freshness

Lock in the taste, nutrients and texture of foods at a wide range of temperatures



Overview

Toplex lidding films are the strongest and most reliable on the market, providing weld sealing for a variety of available bottom webs and tray types, such as PE, PP and AL.

Toplex Locked Seal films feature a high level of product integrity, as well as extended shelf life and excellent machinability, resulting in minimized waste and downtime.

A combination of anti-fog properties, with high-end reverse printing allows enhanced product presentation and visibility on the shelf.

Technology

Toplex Locked Seal films are manufactured using up to 11 layers of film in a combination of blown extrusion technology (up to 9 layers) and lamination process. The lamination is environmentally friendly, using less adhesive solvent. We specially design each layer to achieve different properties – barrier or sealing layers, for example, and layers which provide mechanical strength. After the films are produced, we laminate them to another bi-oriented film to achieve higher gloss, thermal resistance, along with clean and precise cutting of the film on the packaging machine.

Features & Properties

- Hermetic sealing (even through product residue, fatty contamination, and grease) securing product integrity throughout supply chain
- Seals at a wide range of temperatures
- Multipurpose – specially designed to fit different packaging machines, to minimize downtime
- Available with high level reverse printing – up to eight colors
- Can be supplied with laser pre-cut to control the opening mechanism during microwave cooking or direction of the package opening
- Outstanding clarity and gloss
- Anti-fog properties – for better product presentation and clarity
- The gas barrier material, in the high barrier lidding films, has an environmentally friendly, chlorine-free structure

Applications

Masterfully perform on automatic thermoforming, and tray sealing machines

Food Segments

Ideally suited for packaging sliced or chunk cheese; fresh, smoked and processed meat; poultry parts; fish; seafood; and ready meals



Product Range

PRODUCT	THICKNESS [micron]	BARRIER LEVEL	SPECIAL FEATURES	PACKAGING MACHINE
Toplex HB	35-80	HB	<ul style="list-style-type: none"> • Excellent AF • Excellent sealing – locked seal to PE • EP sealing to PP 	<ul style="list-style-type: none"> • Tray sealer (TS) • Thermoforming machine (TFFS)
Toplex HB L-PE	45/60/80	HB	<ul style="list-style-type: none"> • Excellent machinability on flow pack machine • Available with AF • Locked seal to PE 	<ul style="list-style-type: none"> • Tray sealer (TS) • Thermoforming machine (TFFS) • Flow pack machine (HFFS + VFFS)
Toplex HB PP	45/60	HB	<ul style="list-style-type: none"> • Locked seal to PP 	<ul style="list-style-type: none"> • Tray sealer (TS) • Thermoforming machine (TFFS)
Toplex LB	45/60/80	LB	<ul style="list-style-type: none"> • Excellent sealing – locked seal to PE • EP sealing to PP 	<ul style="list-style-type: none"> • Vertical flow pack machine (VFFS) • Tray sealer (TS) • Thermoforming machine (TFFS)
Toplex XT	75-275	HB/MB	<ul style="list-style-type: none"> • Weld seal to PE • Outstanding clarity and gloss • Excellent tear and impact resistance 	<ul style="list-style-type: none"> • Thermoforming machine (TFFS)



www.plastopil.com

EUROPE

Plastopil B.V.

De Steiger 46
1351 AC Almere
The Netherlands

T. +31 36 767 1000
F. +31 36 540 4800

ISRAEL

Plastopil Hazorea Company Ltd.

Hazorea 3658100
Israel

T. +972 4 959 8800
F. +972 4 989 4250

NORTH AMERICA

Plastopil Inc.

838 Lincoln Ave.
Maywood, NJ 07607
U.S.A.

T. +1 551 427 8668
F. +1 201 250 8538